

	COIL/SHEET										Page 1/1				
PLEASE NOTE CURRENT REV	304	304L	316	316L	309	309S	310 310S	321	347	410/410s	430	2205	2507		
ASTM A240/ ASME SA240	.	.	.	.	.	.	.	.	.	.	.	.	.		
ASTM A480/ASTM SA480	.	.	.	.	.	.	.	.	.	.	.	.	.		
AMS QQ-S-766/ QQ-S-766	.	.	.	.	.	.	.	.	.	.	.	.	.		
ASTM A666/ASME SA666	.	.	.	.	.	.	.	.	.	.	.	.	.		
ASTM E112					.	.									
ASTM A923 A, B, C											.	.	.		
AMS SPEC	5513/5511		5524		5523		5521		5510		5512	5504	5503		
UNS	30400/30403		31600/31603		30900/30908		31000/31008		32100		34700	41000	43000	32205/31800	32750
NACE MR 0103 & MR 0175	.	.	.	.	.	.	.	.	.	.	.	.	.		
Corrosion Test: ASTM A262	E		E		E		E		E		E		E		
EN10204 3.1	<b>STATEMENTS REQUIRED ON CERTIFICATES</b>														
COILS NOT TO EXCEED 26,000 LBS	Country of Melt and Manufacture														
COILS TO HAVE 24" ID	Inspector/Quality person's name and title typed and signature on test report														
<i>Colbalt must be noted on test report</i>	Heat treat statement-Time/Temp/Quench														
	ROHS, REACH, LEEDS, PED certifications or declarations must be available														
	Mercury Free/No Weld Repair														
	Fraud and Falsification statement														
	Material supplied in sensitized condition														
	Please note any exceptions to Kfell@pennstainless.com prior to acceptance of orders														

*Dawn M. DeWen*

12/1/2021