

| | Extruded Angle | | | Rolled Angle | | | Welded Angle | | | Page 1/1 | |
|--|--|-------------|-------------|--------------|-------------|-----------|--------------|-------------|-------------|-------------|--|
| | 304 | 304/304L | 316/316L | 304 | 304/304L | 316/316L | 304 | 304/304L | 316/316L | 2205 | |
| PLEASE NOTE CURRENT REV | | | | | | | | | | | |
| ASTM A276/ASME SA276 | • | • | • | • | • | • | | | | | |
| ASTM A479/ASME SA479 | • | • | • | • | • | • | | | | | |
| ASTM A1069 | | | | | | | • | • | • | • | |
| ASTM A480 | | | | | | | • | • | • | • | |
| AMS-QQ-S-763 /QQ-S-763 (current revision) | • | • | • | • | • | • | | | | | |
| AMS Spec | 5639 | 5639/5647 | 5648/5653 | 5639 | 5639-5647 | 5648/5653 | | | | | |
| ASTM A240-Parent Material | | | | | | | • | • | • | • | |
| UNS | 30400 | 30400/30403 | 31600/31603 | 30400 | 30400/30403 | 316/31603 | 30400 | 30400/30403 | 31600/31603 | 31800/32005 | |
| AISI | • | • | • | • | • | • | • | • | • | • | |
| NACE MR 0103 & MR 0175 | • | • | • | • | • | • | • | • | • | • | |
| Corrosion Test: ASTM A262 | A/E | A/E | A/E | A/E | A/E | A/E | A/E | A/E | A/E | A/E | |
| EN 10204 3.1 | STATEMENTS REQUIRED ON CERTIFICATES | | | | | | | | | | |
| <i>Cobalt must be noted on test report</i> | Country of Melt and Mfg | | | | | | | | | | |
| | Inspector/Quality person's name and title typed and signature on cert | | | | | | | | | | |
| | Heat Treat Statement-Time/Temp/Quench | | | | | | | | | | |
| | ROHS, REACH, LEEDS, PED certifications or declarations must be available | | | | | | | | | | |
| | Mercury Free/No Weld Repair | | | | | | | | | | |
| | Fraud and Falsification statement must be on test report | | | | | | | | | | |
| | Material must be supplied in unsensitized condition | | | | | | | | | | |
| | Please note any exceptions to Kfell@pennstainless.com prior to acceptance of orders. | | | | | | | | | | |

Dawn M DeWitt

12/1/2021