

	COIL/SHEET										Page 1/1		
PLEASE NOTE CURRENT REV	304	304L	316	316L	309	309S	310 310S	321	347	410/410s	430	2205	2507
ASTM A240/ ASME SA240	.	.	.	.	.	.	.	.	.	.	.	.	.
ASTM A480/ASTM SA480	.	.	.	.	.	.	.	.	.	.	.	.	.
AMS QQ-S-766/ QQ-S-766	.	.	.	.	.	.	.	.	.	.	.	.	.
ASTM A666/ASME SA666	.	.	.	.	.	.	.	.	.	.	.	.	.
ASTM E112					.	.							
ASTM A923 A, B, C											.	.	.
AMS SPEC	5513/5511		5524		5523		5521	5510	5512	5504	5503		
UNS	30400/30403	31600/31603			30900/30908		31000/31008	32100	34700	41000	43000	32205/31800	32750
NACE MR 0103 & MR 0175	.	.	.	.	.	.	.	.	.	.	.	.	.
Corrosion Test: ASTM A262	E	E	E	E	E	E	E	E	E	E	E	E	E
EN10204 3.1	<b>STATEMENTS REQUIRED ON CERTIFICATES</b>												
COILS NOT TO EXCEED 26,000 LBS	Country of Melt and Manufacture												
COILS TO HAVE 24" ID	Inspector/Quality person's name and title typed and signature on test report												
PAPER INTERLEAVE IN ALL COILS	Heat treat statement-Time/Temp/Quench												
24" ID IN ALL COILS	ROHS, REACH, LEEDS, PED certifications or declarations must be available												
<b>COBALT MUST BE NOTED ON TEST REPORT</b>	Mercury Free/No Weld Repair												
	Fraud and Falsification statement												
	Material supplied in unsensitized condition												
	Please note any exceptions to Kfell@pennstainless.com prior to acceptance of orders												

*Dawn M. DeWlen*

12/1/2021