| Penn Stainles                          | ss Products, Inc. |   |             | Stainle     | ss Steel Shee | t Specifi | cations  |          | F840-2 | 2 Rev D |             |       |       |
|--|-------------------|---|-------------|-------------|---------------|-----------|----------|----------|--------|---------|-------------|-------|-------|
|  |                   |   |             | (           |               |           | Page 1/2 |          |        |         |             |       |       |
| PLEASE NOTE CURRENT REV                | 301 QH-HH-FH      | 304 304L  | 316 316L    | 309 309S    | 310<br>310S   | 321       | 347      | 410/410s | 430    | 439     | 2205        | 2507  | 17-4  |
| ASTM A240/ ASME SA240 Including Cobalt |                   | •   | •           | •           | •             |           | •        |          |        | •       | •           | •     |       |
| ASTM A480/ASTM SA480                   |                   | •   | •           | •           | •             |           | •        | •        |        | •       | •           | •     | •     |
| AMS QQ-S-766/ QQ-S-766                 |                   | •   | •           | •           | •             |           | •        | •        | •      | •       | •           | •     |       |
| ASTM A666/ASME SA666                   |                   | •   | •           |             |               |           | •        |          |        |         |             |       |       |
| ASTM A693/ASME SA693                   |                   |   |             |             |               |           |          |          |        |         |             |       | •     |
| ASTM E112                              |                   | •   | •           | •           | •             |           | •        | •        | •      | •       | •           | •     | •     |
| ASTM A923 A, B, C                      |                   |   |             |             |               |           |          |          |        |         | •           | •     |       |
| AMS SPEC                               | 5518/5519         | 5513/5511   | 5524/5507   | 5523        | 5521          | 5510      | 5512     | 5504     | 5503   |         |             |       | 5647  |
| UNS                                    | 30100/30101       | 30400/30403   | 31600/31603 | 30900/30908 | 31000/31008   | 32100     | 34700    | 41000    | 43000  | 43035   | 32205/31800 | 32750 | 17400 |
| NACE MR 0103 & MR 0175                 |                   | •   | •           | •           | •             |           | •        | •        |        |         | •           | •     |       |
| Corrosion Test: ASTM A262              | Е                 | Е   | Е           | Е           | Е             | Е         | Е        |          |        |         | Е           | Е     | Е     |
| EN10204 3.1                            |                   | STATEMENTS REQUIRED ON CERTIFICATES   |             |             |               |           |          |          |        |         |             |       |       |
| LineMarking-A/SA Spec, Heat,Grade,Size |                   | Country of Melt and Manufacture   |             |             |               |           |          |          |        |         |             |       |       |
| COILS NOT TO EXCEED 26,000 LBS         |                   | Inspector/Quality person's name and title typed and signature on test report  |             |             |               |           |          |          |        |         |             |       |       |
| COILS TO HAVE 20"-24" ID               |                   | Heat treat statement-Time/Temp/Quench   |             |             |               |           |          |          |        |         |             |       |       |
| PAPER INTERLEAVE IN ALL COILS          |                   | ROHS, REACH, LEEDS, PED certifications or declarations must be available  |             |             |               |           |          |          |        |         |             |       |       |
|  |                   | Mercury Free/No Weld Repair   |             |             |               |           |          |          |        |         |             |       |       |
|  |                   | Fraud and Falsification statement  Material supplied in unsensitized condition  Please note any exceptions to Kfell@pennstainless.com prior to acceptance of orders |             |             |               |           |          |          |        |         |             |       |       |
|  |                   |   |             |             |               |           |          |          |        |         |             |       |       |
|  |                   |   |             |             |               |           |          |          |        |         |             |       |       |

Dave M Devlen

2/21/2024

| Penn Stainless Products                | s, Inc.  | Stainless Steel Sheet Specifications F840-2 Rev D                                   |  |  |  |  |  |  |  |  |          |  |  |
|--|----------|---|--|--|--|--|--|--|--|--|----------|--|--|
|  |          | COIL/SHEET  |  |  |  |  |  |  |  |  | Page 2/2 |  |  |
| PLEASE NOTE CURRENT REV                | 904/904L | 254SMO  |  |  |  |  |  |  |  |  |          |  |  |
| ASTM A240/ ASME SA240 Including Cobalt | •        | •   |  |  |  |  |  |  |  |  |          |  |  |
| ASTM A480/ASTM SA480                   | •        | •   |  |  |  |  |  |  |  |  |          |  |  |
| B625                                   | •        |   |  |  |  |  |  |  |  |  |          |  |  |
| SB625                                  | •        |   |  |  |  |  |  |  |  |  |          |  |  |
| B906                                   | •        |   |  |  |  |  |  |  |  |  |          |  |  |
| UNS                                    | N08904   | 31254   |  |  |  |  |  |  |  |  |          |  |  |
| Corrosion Test: ASTM A262              | E        | E   |  |  |  |  |  |  |  |  |          |  |  |
| EN10204 3.1                            |          | STATEMENTS REQUIRED ON CERTIFICATES   |  |  |  |  |  |  |  |  |          |  |  |
| LineMarking-A/SA Spec, Heat,Grade,Size |          | Country of Melt and Manufacture   |  |  |  |  |  |  |  |  |          |  |  |
| COILS NOT TO EXCEED 26,000 LBS         |          | Inspector/Quality person's name and title typed and signature on test report        |  |  |  |  |  |  |  |  |          |  |  |
| COILS TO HAVE 20"-24" ID               |          | Heat treat statement-Time/Temp/Quench   |  |  |  |  |  |  |  |  |          |  |  |
| PAPER INTERLEAVE IN ALL COILS          |          | ROHS, REACH, LEEDS, PED certifications or declarations must be available            |  |  |  |  |  |  |  |  |          |  |  |
|  |          | Mercury Free/No Weld Repair   |  |  |  |  |  |  |  |  |          |  |  |
|  |          | Fraud and Falsification statement   |  |  |  |  |  |  |  |  |          |  |  |
|  |          | Material supplied in unsensitized condition   |  |  |  |  |  |  |  |  |          |  |  |
|  |          | Please note any exceptions to Kfell@pennstainless.com prior to acceptance of orders |  |  |  |  |  |  |  |  |          |  |  |

Davin M. Devlen

2/21/2024