

		Round Bar										Page 1/2
PLEASE NOTE CURRENT REV	303	304	304/304L	316/316L	317L	321	410	416/416HT	420	440C	Alloy 20	630/HT
ASTM A276/ASME SA276		•		•	•	•	•			•		
ASTM A479/ASME SA479	•	•	•	•	•	•	•	•	•	•	•	
ASTM A484/ASME SA484	•	•	•	•	•	•	•					
ASTM A582/ASME SA582	•							•	•			
ASTM A182/ASME SA182 (Forging Sizes)		•	•	•	•	•						
ASTM A193 B8M/ASME SA193 B8M		•	•	•	•	•						
ASTM A320 B8M/ASME SA320 B8M		•	•	•	•	•						
ASTM A564/ASME SA564												•
ASTM B473/ASME SB473											•	
ASTM B472/ASME SB472											•	
AMS QQ-S-763/QQ-S-763 (current revision)		•	•	•	•	•	•		•	•		
AMS Spec	5640 Type 1	5639	5639/5647	5648/5653		5645	5613/5612/2303	5610	5621	5630		5643
UNS	S30300	S30400	S30400/S30403	S31600/S31603	S31700/03	S32100	S41000	S41600	S42000	S44004	N08020	S17400
NACE MR0103/0175		•	•	•	•	•					•	
ASTM A262	E	E	E	E	E	E						
STATEMENTS REQUIRED ON CERTIFICATES												
EN10204 3.1												
Cobalt must be noted on test report		Country of Melt and Country of Manufacture										
		Inspector/ Quality person's name and title typed and signature on cert										
		Heat Treat Statement-Time/Temp/Quench										
		ROHS, REACH, LEEDS, PED certifications or declarations must be available										
		Mercury Free/No Weld Repair										
		Fraud and Falsification statement must be on test report										
		Material must be supplied in unsensitized condition										

Please note any exceptions to Kfeil@pennstainless.com prior to acceptance of orders.

Deane M. Decker

PLEASE NOTE CURRENT REV		Round Bar										Page 2/2
		309	310	347	431	15-5	2205					
ASTM A276/ASME SA276		•	•	•	•		•					
ASTM A479/ASME SA479			•	•	•		•					
ASTM A484/ASME SA484		•	•	•	•		•					
ASTM A582/ASME SA582												
ASTM A182/ASME SA182 (Forging Sizes)				•			•					
ASTM A193 B8M/ASME SA193 B8M				•	•							
A923 C							•					
ASTM A320 B8M/ASME SA320 B8M												
ASTM A564/ASME SA564						•						
ASTM B473/ASME SB473												
ASTM B472/ASME SB472												
AMS QQ-S-763/QQ-S-763 (current revision)		•	•	•								
AMS Spec			5651	5646	5628	5659						
UNS		S30900/08	S31000/08	S34200/09	S431000	S15500	S32205/31803					
NACE MR0103/0175		•	•	•			•					
ASTM A262		•	•	•								
EN10204 3.1												
<i>Cobalt must be noted on test report</i>		STATEMENTS REQUIRED ON CERTIFICATES										
		Country of Melt and Country of Manufacture										
		Inspector/Quality person's name and title typed and signature on cert										
		Heat Treat Statement-Time/Temp/Quench										
		ROHS, REACH, LEEDS, PED certifications or declarations must be available										
		Mercury Free/No Weld Repair										
		Fraud and Falsification statement must be on test report										
		Material must be supplied in unsensitized condition										
		Please note any exceptions to Kfell@penstainless.com prior to acceptance of orders.										

Dawn M. DeLun

7/17/2025