

Penn Stainless Products, Inc.			Stainless Steel Sheet Specifications										F840-2 Rev D				
PLEASE NOTE CURRENT REV	301 QH-HH-FH	304	COIL/SHEET										Page 1/2				
			304L	316	316L	309	309S	310	310S	321	347	410/410S			430	439	2205
ASTM A240/ ASME SA240 Including Cobalt																	
ASTM A480/ASTM SA480	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
AMS QQ-S-766/ QQ-S-766		*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
ASTM A666/ASME SA666	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
ASTM A693/ASME SA693																	*
ASTM E112	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
ASTM A923 A, B, C																	*
AMS SPEC	5518/5519	5513/5511	5524/5507	5523	5521	5510	5512	5504	5503								5647
UNS	30100/30101	30400/30403	31600/31603	30900/30908	31000/31008	32100	34700	41000	43000	43035	32205/31800	32750	17400				
NACE MR 0103 & MR 0175	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*	*
Corrosion Test: ASTM A262	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E
EN10204 3.1	STATEMENTS REQUIRED ON CERTIFICATES																
LineMarking-A/SA Spec, Heat,Grade,Size	Country of Melt and Manufacture																
COILS NOT TO EXCEED 26,000 LBS	Inspector/Quality person's name and title typed and signature on test report																
COILS TO HAVE 20"-24" ID	Heat treat statement-Time/Temp/Quench																
PAPER INTERLEAVE IN ALL COILS	ROHS, REACH, LEEDS, PED certifications or declarations must be available																
	Mercury Free/No Weld Repair																
	Fraud and Falsification statement																
	Material supplied in unsensitized condition																
	Please note any exceptions to K.fell@pennstainless.com prior to acceptance of orders																

Dawn M. Decker

2/21/2024

Penn Stainless Products, Inc.		Stainless Steel Sheet Specifications		F840-2 Rev D		
PLEASE NOTE CURRENT REV		COIL/SHEET				Page 2/2
ASTM A240/ ASME SA240 Including Cobalt		904/904L	234S30			
ASTM A480/ASTM SA480		*	*			
B625		*	*			
SB625		*				
B906		*				
UNS		N08904	31254			
Corrosion Test: ASTM A262		E	E			
EN10204 3.1						
STATEMENTS REQUIRED ON CERTIFICATES						
Line Marking-A/SA Spec, Heat, Grade, Size		Country of Melt and Manufacture				
COILS NOT TO EXCEED 26,000 LBS		Inspector/Quality person's name and title typed and signature on test report				
COILS TO HAVE 20"-24" ID		Heat treat statement-Time/Temp/Quench				
PAPER INTERLEAVE IN ALL COILS		ROHS, REACH, LEEDS, PED certifications or declarations must be available				
		Mercury Free/No Weld Repair				
		Fraud and Falsification statement				
		Material supplied in unsensitized condition				
		Please note any exceptions to K.fell@pennstainless.com prior to acceptance of orders				

Dawn M. Decker

2/21/2024