**Penn Stainless Products, Inc.** **Stainless Steel Sheet Specifications** **F840-2 Rev F**



| | | COIL/SHEET | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **PLEASE NOTE CURRENT REV** | 301 QH-HH-FH | 304 304L | 316 316L | 309S/309H | 310 310S | 321 | 347 | 410/410S | 430 | 439 | 2205 | 2507 | 17-4 |
| ASTM A240/ ASME SA240 **Including Cobalt** | | • | • | • | • | • | • | | • | • | • | • | |
| ASTM A480/ASTM SA480 | • | • | • | • | • | • | • | • | • | • | • | • | • |
| AMS QQ-S-766/ QQ-S-766 | | • | • | • | • | • | • | • | • | | • | • | |
| ASTM A666/ASME SA666 | • | • | • | | | • | • | | | | | | |
| ASTM A693/ASME SA693 | | | | | | | | | | | | | • |
| ASTM E112 | • | • | • | • | • | • | • | • | • | • | • | • | |
| ASTM A923 A, B, C | | | | | | | | | | | • | • | |
| AMS SPEC | 5518/5519 | 5513/5511 | 5524/5507 | 5523 | 5521 | 5510 | 5512 | 5504 | 5503 | | | | 5604 |
| UNS | 30100/30101 | 30400/30403 | 31600/31603 | 30900/30908 | 31000/31008 | 32100 | 34700 | 41000 | 43000 | 43035 | 32205/31800 | 32750 | 17400 |
| NACE MR 0103 & MR 0175 | • | • | • | • | • | • | • | • | • | | • | • | |
| Corrosion Test: ASTM A262 | E | E | E | E | E | E | E | | | | | | |
| EN10204 3.1 | | **STATEMENTS REQUIRED ON CERTIFICATES** | | | | | | | | | | | |
| **LineMarking-A/SA Spec, Heat,Grade,Size** | | Country of Melt and Manufacture | | | | | | | | | | | |
| COILS NOT TO EXCEED 26,000 LBS | | Inspector/Quality person's name and title typed and signature on test report | | | | | | | | | | | |
| COILS TO HAVE 20"-24" ID | | Heat treat statement-Time/Temp/Quench | | | | | | | | | | | |
| PAPER INTERLEAVE IN ALL COILS | | ROHS, REACH, LEEDS, PED certifications or declarations must be available | | | | | | | | | | | |
| | | Mercury Free/No Weld Repair | | | | | | | | | | | |
| | | Fraud and Falsification statement | | | | | | | | | | | |
| | | Material supplied in unsensitized condition | | | | | | | | | | | |
| | | Please note any exceptions to Kfell@pennstainless.com prior to acceptance of orders | | | | | | | | | | | |

Dana M Beuler

5/22/2026

| Penn Stainless Products, Inc. | | Stainless Steel Sheet Specifications | | | | | | | | | | F840-2 RevE | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | COIL/SHEET | | | | | | | | | | Page 2/2 | |
| **PLEASE NOTE CURRENT REV** | | 904/904L | 254SMO | 416 | 405 | | | | | | | | |
| ASTM A240/ ASME SA240 **Including Cobalt** | | • | • | | • | | | | | | | | |
| ASTM A480/ASTM SA480 | | • | • | • | • | | | | | | | | |
| ASTM A582 CHEM ONLY | | | | • | | | | | | | | | |
| ASTM A895 | | | | • | | | | | | | | | |
| B625 | | • | | | | | | | | | | | |
| SB625 | | • | | | | | | | | | | | |
| B906 | | • | | | | | | | | | | | |
| AMS SPEC | | | | 5610 | | | | | | | | | |
| UNS | | N08904 | 31254 | 41600 | 40500 | | | | | | | | |
| Corrosion Test: ASTM A262 | | E | E | | | | | | | | | | |
| EN10204 3.1 | | **STATEMENTS REQUIRED ON CERTIFICATES** | | | | | | | | | | | |
| **LineMarking-A/SA Spec, Heat,Grade,Size** | | Country of Melt and Manufacture | | | | | | | | | | | |
| COILS NOT TO EXCEED 26,000 LBS | | Inspector/Quality person's name and title typed and signature on test report | | | | | | | | | | | |
| COILS TO HAVE 20"-24" ID | | Heat treat statement-Time/Temp/Quench | | | | | | | | | | | |
| PAPER INTERLEAVE IN ALL COILS | | ROHS, REACH, LEEDS, PED certifications or declarations must be available | | | | | | | | | | | |
| | | Mercury Free/No Weld Repair | | | | | | | | | | | |
| | | Fraud and Falsification statement | | | | | | | | | | | |
| | | Material supplied in unsensitized condition | | | | | | | | | | | |
| | | Please note any exceptions to Kfell@pennstainless.com prior to acceptance of orders | | | | | | | | | | | |

2/1/2026

Dawn M Devlin